

# PILE DRIVERS

## SG-75

### FEATURES

- Designed to match the capabilities of larger excavators and to combine a robust structure with excellent pile handling characteristics.
- Fitted with heavy-duty arms/clamps capable of driving a wide range of piles including sheet piles, H-piles, tubular steel piles and other pile sections.
- High frequency pile driver with variable eccentric moment.
- Based on the Movax Modular System (MMS™). The unit is always equipped with one of the standard arm/clamp systems and the bottom clamp. Customised arms and clamps are available upon special request.
- Controlled with the MOVAX Control System (MCS™)
- Available with the MOVAX Information Management System (MIMS™).



### TECHNICAL DATA

Weight (excl. adapter) *	kg	3370 - 3620
Height	mm	2615
Depth	mm	1290 - 1665
Width	mm	1270
Engine power, min, Tier III / Tier IV	kW	180 / 200
Return pressure, max	bar	5
Pressure setting	bar	350
Frequency	1/min	2300 - 3000
Eccentric moment	kgm	7.6
Centrifugal force, max	kN	750
Ground vibration		Normal
Oil flow rate	l/min	0 - 0
Driving method		Vibration
Swing angle	°	+/- 360
Tilt angle	°	+/- 30

\* with standard bottom clamp, exact weight depends on the side arm/clamp system

### SUITABLE PILES

#### TYPES AND DIMENSIONS

Sheet pile	width mm	400-1200
	depth mm	265
H-beam	size	H180-H500
Timber pile	mm	Ø 160-420
Tubular pile, tubes *	mm	up to 762

\* up to 1220 mm diameter with modular tube arms and tandem bottom clamp



#### LENGTH & WEIGHT

6m / 2800kg

12m / 1900kg

16m / 1300kg